

# Latest Generation Beacons

Intrinsically safe accreditation: IECEx and ATEX Ex ic IIC T4 Gc

## **\* Lighter \* Brighter**

# **New Industry Leader**

### LIGHTWEIGHT & 4 AA BATTERIES

For both compact and standard sizes

### ADVANCED LENS & BRIGHTER LEDs


Precision omnidirectional lens boosting LED output

## **IMPROVED SWITCHING**

Simpler, Faster, Better

### PERSONAL PROTECTION & DUTY OF CARE

Brighter and choice of colours to suit work situation with belt clip or lanyard



## Hare AT290

Eflare Corporation Pty Ltd Victoria, Australia Eflare Safety Beacon CE & II 3G Ex ic II C T4 Gc -20°C≤Ta≤+40°C ITS10ATEX 27129 IECEx TSA 11.0023 S/N 006059 YR 2011

Effare Corporation Pty Ltd www.effarecorp.com Market and Alexandre State Construction and the state of the State Construction and the state of the State Construction and the State State Construction and the State Constructions and the State

Hare AT280

Close to actual size

#### www.eflarecorp.com

 $\bigcirc$ 

# **Latest Generation** Beacons



Product Range									
Compact Part No	Standard Part No	LED Qty	Function	Candela	Weight (Inc Batteries)	Height	Flash Rate	Battery	Battery Life
AT280R	AT290R	8	Flash or Steady On	Flash = 60 Steady On =20	Compact = 240g Standard = 260g	Compact = 15cm Standard = 20cm	165-185 fpm	4 x AA Cell	20+ Hours
AT280A	AT290A			Flash = 70 Steady On =25					
AT280B	AT290B			Flash = 18 Steady On = 10					
AT280G	AT290G			Flash = 40 Steady On =13					
AT280W	AT290W			Flash = 80 Steady On = 25					
AT 283RB	AT 293RB	4 + 4	Dual Flash	30					
AT 283RA	AT 293RA			35					
AT 283RW	AT 293RW			40					
AT 283RG	AT 293RG			30					
AT 283BW	AT 293BW			40					
AT 283GW	AT 293GW			40					
AT 283AB	AT 293AB			35					
AT 283BG	AT 293BG			20					
AT 283GA	AT 293GA			35					
AT 283AW	AT 293AW			40					

Product Definitions AT = Flash or Steady On in single colour (flash only in dual flash models) TF = Torch option added to either (dual) flash or steady on unit.

Letter at the end denotes LED colour(s) Units come in eitehr Compact height (15cm) or Standard height (20cm) Dual flash candela measurements based on the dominant colour

#### Accessories



Cone Mount

**Rubber Base** 

Mount







Mount

Aviation Base Mount



Compact Magnetic Base



Magnetic Base Floatation Collar



Special Order Products TF units with torch option 281 or 291 - single colour flash only 282 or 292 - single colour steady on only

www.eflarecorp.com