Version No. 13450-14B Issue Date: October 23, 2014 Supersedes Date: March 7, 2014 OSHA HCS-2012 / GHS

Section 1: IDENTIFICATION

Product Name: Simple Green® Anti-Spatter

Additional Names:

Manufacturer's Part Number: *Please refer to Section 16

Recommended Use: Prespray to protect surfaces from spatter buildup during welding.

Restrictions on Use: Do not use on non-rinsable or asphalt surfaces

Company: Sunshine Makers, Inc. **Telephone:** 800-228-0709 ● 562-795-6000 *Mon – Fri, 8am – 5pm PST*

15922 Pacific Coast Highway **Fax:** 562-592-3830

Huntington Beach, CA 92649 USA Email: info@simplegreen.com

Emergency Phone: Chem-Tel 24-Hour Emergency Service: 800-255-3924

Section 2: HAZARDS IDENTIFICATION

This product is classified as hazardous (Eye Corrosive/Irritant - Category 2B) under 2012 OSHA Hazard Communication Standards (29 CFR 1910.1200).

OSHA HCS 2012 Label Elements

Signal Word: Warning Hazard Symbol(s)/Pictogram(s): None required

Hazard Statements:

H320 - Causes Eye Irritation.

Precautionary Statements:

P264 – Wash hands thoroughly after handling.

P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 – If eye irritation persists: Get medical advice.

Hazards Not Otherwise Classified (HNOC): No hazards not otherwise classified were identified

Other Information: None Known.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredient</u>	CAS Number	Percent Range
Water	7732-18-5	> 87%*
Triethanolamine	102-71-6	≤ 5%*
Ethoxylated Alcohol / Quaternary Amine Mixture	Proprietary	≤ 5%*
Propylene Glycol Butyl Ether	5131-66-8	< 1%*
Tetrapotassium Pyrophosphate	7320-34-5	< 1%*
Sodium Silicate	1344-09-8	< 1%*

^{*}specific percentages of composition are being withheld as a trade secret

Section 4: FIRST-AID MEASURES

Inhalation: Not expected to cause respiratory irritation. If adverse effect occurs, move to fresh air. **Skin Contact:** Not expected to cause skin irritation. If adverse effect occurs, rinse skin with water.

Eye Contact: Causes eye irritation. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

Ingestion: May cause upset stomach. Drink plenty of water to dilute. See section 11.

Most Important Symptoms/Effects, Acute and Delayed: None known.

Indication of Immediate Medical Attention and Special Treatment Needed, if necessary: Treat symptomatically

Version No. 13450-14B Issue Date: October 23, 2014 Supersedes Date: March 7, 2014 OSHA HCS-2012 / GHS

Section 5: FIRE-FIGHTING MEASURES

Suitable & Unsuitable Extinguishing Media: Specific Hazards Arising from Chemical: Special Protective Actions for Fire-Fighters: Use Dry chemical, CO2, water spray or "alcohol" foam. Avoid high volume jet water. In event of fire, fire created carbon oxides and oxides of phosphorus may be formed. Wear positive pressure self-contained breathing apparatus; Wear full protective

clothing.

This product is non-flammable. See Section 9 for Physical Properties.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

For non-emergency personnel: See section 8 – personal protection.

For emergency responders: Avoid eye contact. Safety goggles suggested if splashing or misting is likely to occur.

Environmental Precautions: Do not allow into open waterways and ground water systems.

Methods and Materials for Containment and Clean Up: Dike or soak up with inert absorbent material. See section 13 for disposal considerations.

Section 7: HANDLING AND STORAGE

Precautions for Safe Handling: Ensure adequate ventilation. Keep out of reach of children. Keep away from heat, sparks, open flame and direct sunlight. Do not pierce any part of the container. Do not mix or contaminate with any other chemical. Do not eat, drink or smoke while using this product.

Conditions for Safe Storage including Incompatibilities: Keep container tightly closed. Keep in cool dry area. Avoid prolonged exposure to sunlight. Do not store at temperatures above 109°F (42.7°C). If separation occurs, mix the product for reconstitution.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limit Values: Triethanolamine (102-71-6) 5 mg/m³ PEL California

Diethanolamine (111-42-2) 3 ppm TWA; 15 mg/m³ TWA Connecticut, Michigan, Minnesota, OSHA,

Tennessee, Vermont, Washington

0.46 ppm PEL; 2 mg/m³ PEL California

6 ppm STEL Washington

Appropriate Engineering Controls: Showers, eyewash stations, ventilation systems

Individual Protection Measures / Personal Protective Equipment (PPE)

Eye Contact: Use protective glasses or safety goggles if splashing or spray-back is likely.

Respiratory: Use in well ventilated areas or local exhaust ventilations when cleaning small spaces.

Skin Contact: Use protective gloves (any material) when used for prolonged periods or dermally sensitive.

General Hygiene Considerations: Wash thoroughly after handling and before eating or drinking.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:Clear LiquidPartition Coefficient: n-octanol/water:Not determinedOdor:No added odorAutoignition Temperature:Non-flammable

Odor Threshold: Not determined Decomposition Temperature: 109°F

pH: 9 – 10.55 **Viscosity:** Like water

Freezing Point: 0°C (32°F) Specific Gravity: 1.00 - 1.01

Boiling Point & Range: 98°C (210°F) **VOCs:** **Water & fragrance exemption in calculation

Flash Point: > 212°F SCAQMD 304-91 / EPA 24: Not tested

Evaporation Rate: Not determined CARB Method 310**: 5 g/L 0.042 lb/gal 0.5%

Flammability (solid, gas): Not applicable SCAQMD Method 313: Not tested

Upper/Lower Flammability or Explosive Limits: Not applicable VOC Composite Partial Pressure: Not tested

Page 2 of 5

Version No. 13450-14B Issue Date: October 23, 2014 Supersedes Date: March 7, 2014 OSHA HCS-2012 / GHS

Section 9: PHYSICAL AND CHEMICAL PROPERTIES - continued

Vapor Pressure :Not determinedRelative Density:8.34 – 8.42 lb/galVapor Density:Not determinedSolubility:100% in water

Section 10: STABILITY AND REACTIVITY

Reactivity: Non-reactive.

Chemical Stability: Stable under normal conditions 70°F (21°C) and 14.7 psig (760 mmHg).

Possibility of Hazardous Reactions: None known.

Conditions to Avoid: Excessive heat or cold.

Incompatible Materials: Do not mix with oxidizers, acids, bathroom cleaners, or disinfecting agents.

Hazardous Decomposition Products: Normal products of combustion - CO, CO2, oxides of phosphorus.

Section 11: TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Inhalation - Overexposure may cause headache.

Skin Contact - Not expected to cause irritation.

Eye Contact - Causes eye irritation.

Ingestion - May cause upset stomach.

Symptoms related to the physical, chemical and toxicological characteristics: no symptoms expected under typical use conditions. Delayed and immediate effects and or chronic effects from short term exposure: no symptoms expected under typical use conditions. Delayed and immediate effects and or chronic effects from long term exposure: headache, dry skin, or skin irritation may occur. Interactive effects: Not known.

Numerical Measures of Toxicity

Acute Toxicity: Oral LD₅₀ (rat) > 5 g/kg body weight

Dermal LD₅₀ (rabbit) > 5 g/kg body weight

Calculated via OSHA HCS 2012 / Globally Harmonized System of Classification and Labelling of Chemicals

Skin Corrosion/Irritation: Non-irritant per Dermal Irritection® assay modeling. *No animal testing performed.* **Eye Damage/Irritation:** Irritant per Ocular Irritection® assay modeling. *No animal testing performed.*

Germ Cell Mutagenicity: Mixture does not classify under this category.

Carcinogenicity: Volume of ingredients does not trigger or classify under this category. This product contains trace

amounts of Diethanolamine (IARC 2B and ACGIH A3)

Reproductive Toxicity: Mixture does not classify under this category.

STOT-Single Exposure: Mixture does not classify under this category.

STOT-Repeated Exposure: Mixture does not classify under this category.

Aspiration Hazard: Mixture does not classify under this category.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Volume of ingredients used does not trigger toxicity classifications under the Globally Harmonized System of

Classification and Labelling of Chemicals.

Aquatic: Not tested on finished formulation.

Terrestrial: Not tested on finished formulation.

Persistence and Degradability: Based on similar formulations, expected to be Readily Biodegradable

Bioaccumulative Potential:No data available.Mobility in Soil:No data available.Other Adverse Effects:No data available.

Version No. 13450-14B Issue Date: October 23, 2014 Supersedes Date: March 7, 2014 OSHA HCS-2012 / GHS

Section 13: DISPOSAL CONSIDERATIONS

Unused or Used Liquid: May be considered hazardous in your area depending on usage and tonnage of disposal – check with local, regional, and or national regulations for appropriate methods of disposal.

Empty Containers: May be offered for recycling.

Never dispose of used degreasing rinsates into lakes, streams, and open bodies of water or storm drains.

Section 14: TRANSPORT INFORMATION

U.N. Proper Shipping Name: Cleaning Compound, Liquid NOI

Transport Hazard Class(es):Not applicableNMFC Number:48580-3Packing Group:Not applicableClass:55

Environmental Hazards: Marine Pollutant - NO

Transport in Bulk (according to Annex II of MARPOL 73/78 and IBC Code): Unknown.

Special precautions which user needs to be aware of/comply with, in connection None known.

with transport or conveyance either within or outside their premises:

U.S. (DOT) / Canadian TDG: Not Regulated for shipping. ICAO/ IATA: Not classified as Hazardous IMO / IDMG: Not classified as Hazardous ADR/RID: Not classified as Hazardous

Section 15: REGULATORY INFORMATION

All components are listed on: TSCA and DSL Inventory.

SARA Title III: Sections 311/312 – Not applicable.

Sections 313 Superfunds Amendments and Reauthorizations Act of 1986 - Diethanolamine (1142-2) < 0.01%

Sections 302 – Not applicable.

Clean Air Act (CAA): Triethanolamine (102-71-6), Diethanolamine (111-42-2), Propylene Glycol Butyl Ether (5131-66-8)

<u>Clean Water Act (CWA):</u> Not applicable

CERCLA: Diethanolamine (111-42-2) 100 lb RQ

State Right To Know Lists: Triethanolamine (102-71-6) Massachusetts, New Jersey, Pennsylvania

Diethanolamine (111-42-2) Massachusetts, New Jersey, Pennsylvania

CA Proposition 65: Diethanolamine (111-42-2) < 0.01%

Texas ESL:

Triethanolamine 5 μg/m³ long term 50 μg/m³ short term 102-71-6 730 µg/m³ short term Propylene Glycol Butyl Ether 5131-66-8 73 μg/m³ long term $5 \mu g/m^3 long term$ 50 μg/m³ short term Tetrapotassium Pyrophosphate 7320-34-5 Sodium Silicate 1344-09-8 5 μg/m³ long term 50 μg/m³ short term Diethanolamine $1 \mu g/m^3 long term$ 10 μg/m³ short term 111-42-2

Section 16: OTHER INFORMATION

 Size
 Item Number
 UPC

 32 oz
 1400000113452
 0433

32 oz 1400000113452 043318134524 32 oz, 12 per case 13452 & 1410001213452 043318134524 5 Gallon 13457 & 1400000113457 043318134579

USA part numbers listed only. Not all part numbers listed. USA part numbers may not be valid for international sale.

Version No. 13450-14B Issue Date: October 23, 2014 Supersedes Date: March 7, 2014 OSHA HCS-2012 / GHS

Section 16: OTHER INFORMATION - continued

NFPA:

Health – Eye Irritant Stability – Stable Flammability – Non-flammable Special - None



Acronyms

NTP National Toxicology Program IARC International Agency for Research on Cancer
OSHA Occupational Safety and Health Administration CPSC Consumer Product Safety Commission
TSCA Toxic Substances Control Act DSL Domestic Substances List

Prepared / Revised By: Sunshine Makers, Inc., Regulatory Department.

This SDS has been revised in the following sections: Revised MSDS to SDS format

DISCLAIMER: The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.